

“W” Standard Coil Weather-Proofing (obsolete)

Originally noted for obsolescence: Jan. 1, 2002

Updated: March 10, 2008

The older “W” option, standard coil weather-proofing method is being discontinued in favor of the newer Series “E” Water/Weather Resistant Coils described on pages 3.400.1.

The new “E” Series coils provide IP69K weather resistance for our standard solenoid and proportional valve products. The E-coil has become our preferred coil and is a proven, reliable and cost-effective solution for severe environmental applications. E-coils are available in lead-wire, Deutsch, Metri-Pack and DIN connector versions.

The older “W” weather resistant, sealed stem tube, solenoid valve option is being discontinued. Stem tubes and adapters used in these older-design products are being phased out due to lower usage and increasing cost. The standard valve with the E-coil option provides superior performance, functional interchangeability and a very competitive price.

The “W” weather resistant solenoid valves will no longer be supported for production applications. All combination valves and manifold assemblies using the “W” option products must be re-specified.

The older “W” option weather-proofing will continue to be available as service parts through 2008, unless otherwise negotiated. Please note that pricing will be adjusted and lead-times will be extended as we reduce supporting inventories for these products.

“W” Option Product Information

Model Group	Armature Type	Installation Type	Field Conversion	Service Kit P/N
PV7x-xx	Proportional	E/H	Yes/All	6260145
SL08-22	Pull	A	No	6260100
SL38/58-22	Pull	A	Yes	6260130
SV08-20, 22, 24, 25, 26, 30, 31, 33, 40, 41, 42, 44, 45, 46	Pull	A	No	6260100
SV08-21, 23	Push	B	No	6260105
SV08-47A, 47C, 47D	Push/Pull	C/D	Yes/All	C-6260111 D-6260106
SV10-20, 22, 24, 25, 31, 33, 34, 40, 41, 42, 43, 44, 45	Pull	A/F	No	A-6260130 F-6260110
SV10-21, 23	Push	B/G	No	B-6260135 G-6260115
SV10-47A, 47B, 47C, 47D	Push/Pull	C/D	No	C-6260200 D-TBD
SV38/58-26	Pull	A/F	No	A-6260130 F-6260110
SV58-20, 22, 24, 25, 30, 40, 41, 42, 44	Pull	A/F	No	A-6260130 F-6260110
SV58-21, 23	Push	B	No	6260135
SV12-20, 22	Pull	A	Yes/All	6260130
SV12-21, 23	Push	B	Yes/All	6260135
SV16-20, 22	Pull	A	Yes/All	6260130
SV16-21, 23	Push	B	Yes/All	6260135

NOTE: Torque weather-proofing nuts to 0.07–0.10 Nm (7–10 ft. lbs.) max.