


D COIL 10 SIZE


Overview



Construction

Magnet wire wound on a molded 30% glass filled bobbin framed in steel and encapsulated with 30% glass filled polyester resin.

Dimensions



ALL DIMENSIONS ARE FOR REFERENCE ONLY

Coil Part Numbers

Standard Coils

Old Number	New Number	Code	Vols	Termination	UL	Diode
4301891	R935003555	10 DR/D	10	DEUTSCH DT04-2P	false	true
6357012	R930091154	12 DL	12	DUAL LEADS	false	false
6359732	R930091158	12 DL/D/W	12	MALE 2-PIN WEATHERPACK	false	true
6359412	R930091156	12 DL/W	12	MALE 2-PIN WEATHERPACK	false	false
4301892	R930091013	12 DR/D	12	DEUTSCH DT04-2P	false	true
4301862	R930091008	12 DR/Z	12	DEUTSCH DT04-2P	false	true
4301893	R930091014	20 DR/D	20	DEUTSCH DT04-2P	false	true
6359739	R935060580	24 DL/D/W	24	MALE 2-PIN WEATHERPACK	false	true

D COIL 10 SIZE

Old Number	New Number	Code	Vols	Termination	UL	Diode
6359424	R930091157	24 DL/W	24	MALE 2-PIN WEATHERPACK	false	false
6355024	R935060506	24 DP	24	CONDUIT	false	false
4301894	R930091015	24 DR/D	24	DEUTSCH DT04-2P	false	true

Optional Coils

Old Number	New Number	Code	Vols	Termination	UL	Diode
6356010	R930091152	10 DG	10	DIN 43650	true	false
6352010	R935060478	10 DL	10	DUAL LEADS	true	false
6351010	R930091144	10 DS	10	DUAL SPADE PER SAE J858a	true	false
6356012	R930091153	12 DG	12	DIN 43650	true	false
6352012	R930091149	12 DL	12	DUAL LEADS	true	false
4301612	R901539386	12 DR	12	DEUTSCH DT04-2P	true	false
6351012	R930091145	12 DS	12	DUAL SPADE PER SAE J858a	true	false
6351020	R930091146	20 DS	20	DUAL SPADE PER SAE J858a	true	false
6356024	R935060519	24 DG	24	DIN 43650	true	false
6352024	R930091150	24 DL	24	DUAL LEADS	true	false
4301624	R930091005	24 DR	24	DEUTSCH DT04-2P	true	false
6351024	R930095902	24 DS	24	DUAL SPADE PER SAE J858a	true	false
6351036	R930091147	36 DS	36	DUAL SPADE PER SAE J858a	true	false

MODEL CODE EXAMPLE:

SV10-XX-0-X-12DX/X

CAVITY AND COIL SIZE

VOLTAGE

CONNECTOR

DIODE TYPE