

Flow regulator 3 way, combination type pressure compensated


VRFC3C

0M.42.03.50 - Y

RE 18309-52

Edition: 03.2016

Replaces: 04.2010



Description




A constant priority flow, regardless of system pressures, is established from E to P, while a minimum pressure differential of appr. 5 bar (70 psi) exists between the two ports. While the regulated priority flow from P is used in the priority circuit, the flow supplied to E in excess of priority is by-passed to port B and can be sent to power other actuators. Priority flow can be varied from zero (Closed) to the nominal maximum rating for the valve (Open). Reverse flow from P to E is limited by the selected opening of the restrictor and is not pressure compensated. Reverse flow from B is not permitted.

Technical data

Operating pressure	210 bar (3000 psi)
QE= max. inlet flow "E" port (see "Dimensions")	
QP= max. regulated flow "P" port (see "Dimensions")	
Weight	see "Dimensions"
Manifold material	Aluminium
Note: aluminium bodies are often strong enough for operating pressures exceeding 210 bar (3000 psi), depending from the fatigue life expected in the specific application. If in doubt, consult our Service Network.	
Fluid	Mineral oil (HL, HLP) according DIN 51524
Fluid temperature range	-30 °C to 100 (-22 to 212 °F)
Viscosity range	5 to 800 mm ² /s (cSt)
Recommended degree of fluid contamination	Class 19/17/14 according to ISO 4406
Other technical data	see data sheet 18350-50

Note: for applications outside these parameters, please consult us.

Characteristic curve



Ordering code

0M.42.03	50	Y
----------	----	---

Flow regulator
3 way, combination type
pressure compensated

Adjustments

Lever with built in friction clutch


Port sizes	E - B - P
02	G 3/8
03	G 1/2
04	G 3/4

Preferred types

Type	Material number
0M420350020000A	R930000033
0M4203500300000	R930004322
0M4203500400000	R930004323

Type	Material number

Dimensions



Bosch Rexroth Oil Control S.p.A.

Via Leonardo da Vinci 5
P.O. Box no. 5
41015 Nonantola – Modena, Italy
Tel. +39 059 887 611
Fax +39 059 547 848
compact-hydraulics-pib@boschrexroth.com
www.boschrexroth.com/compacthydraulics

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth Oil Control S.p.a.. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging. Subject to change.